



RED-MARK / NEO-GLO R-3M(NT) Rinse Water

R-3M (NT) is a cleaning water used for water-wash processing. It is used during water washing of excess penetrant in non-destructive testing.

■ FEATURES

- Designed with spray pressure specifications that reduce the risk of overwashing.
- Aerosol type is also available that is easy to carry and use.

■ PROPERTIES

| | |
|------------------|---------------------------|
| Color | Colorless and transparent |
| Odor | No odor |
| Flash Point | - |
| Fire Service Act | - |

■ SPECIFICATION CONFORMANCE

* Please contact us regarding compliance to the latest standards and standards not listed in this TDS.

RED-MARK / NEO-GLO R-3M(NT) Rinse Water

■ APPLICATIONS

- Welds
- Castings
- Forgings
- Pressure vessels
- General metals

■ SPECIFICATION

| | |
|--------------------------|---|
| NDT Method | Penetrant Testing (PT) / Rinse Water |
| Type | Type I (Fluorescent) / Type II (Dye) |
| Method | A (Water-washable) |
| Storage Temperature | Can : 34°F~104°F(0°C~40°C) / Aerosol : less than 104°F(40°C) |
| Usage Temperature | 34°F~122°F/1°C~50°C |
| Quality assurance period | Can: 2 years from the manufacturing month Aerosol: 3 years from the manufacturing month |
| Disposal | Aerosol : After using up the contents, press the button outside in a fire-free area until the spray sound disappears, vent the gas completely. Can : Dispose empty can in a safe manner in accordance with local/national regulations. |

■ CONTAINER

Can Type: 3.8L and 18L can

Aerosol Type: 450 type Aerosol

■ SERVICE/CONTACT

Please be sure to read the SDS (Safety Data Sheet) before use.

Please download the SDS from our website or contact our nearest sales office or distributor.

For other inquiries about our products, please contact our nearest sales office.

Contact us →

