

MAGNATRON Resmine C Rust Inhibitor

Resmine-C is a rust inhibitor added to magnetic particle suspension. It prevents the test specimen from rusting for several days after inspection. Adjust the concentration of the rust inhibitor according to the required rust prevention period of the test specimen.

It is particularly effective for cast and forged products, with a recommended concentration of 0.5-5% added to the inspection liquid.

FEATURES

· Provides high rust prevention performance.

PROPERTIES

Color	Colorless and transparent
Odor	Mild ammonia odor

SPECIFICATION CONFORMANCE

* Please contact us regarding compliance to the latest standards and standards not listed in this TDS.



MAGNATRON Resmine C Rust Inhibitor

APPLICATIONS

- · Rolled materials
- Welded parts
- · Castings and forgings
- Material inspection
- · Machined components

■ SPECIFICATION

NDT Method	Magnetic Particle Testing (MT) /Antirust
Storage	34°F~104°F/1°C~40°C
Temperature	
Usage Temperature	40°F~134°F/5°C~57°C
Recommended	0.5~5%
Concentration	
Quality assurance	1 year from the manufacturing date
period	
Disposal	Dispose empty can in a safe manner in accordance with local/national
	regulations.

CONTAINER

Can Type: 3.8L and 18L can

■ SERVICE/CONTACT

Please be sure to read the SDS (Safety Data Sheet) before use.

Please download the SDS from our website or contact our nearest sales office or distributor.

For other inquiries about our products, please contact our nearest sales office.

Contact us →

